

PINKSLIP

Friction-Reducing Device



Parameter	Spec
Device Part Number	633010A, (1 pkg-10 Pink Slips) 633011A, (1 case, 10 pkgs-100 Pink Slips)
Device Name	Pink Slip®
Device Description	Single patient use, friction reducing device used to aid in repositioning, lateral transfer and many other patient maneuvers. It is individually packaged and recyclable.
Unit Description	1 Pink Slip®
Unit per Package	10
Unit per Case	100
Unit Dimensions	33 x 40 inches
Unit Weight (shipping)	2.4 ounces
Package Dimensions	3.75W x 4.87H x 10L inches (1 pkg-10 Pink Slips)
Case Dimensions	10W x 9.5H x 18L inches (1 case, 10 pkgs-100 Pink Slips)
HIBC Code	M668633010 (pkg), M668633011 (case)
Radiolucent	Yes- it has been verified to be radiolucent
Health/Safety	Contains no Latex or PVC
Recyclable	Yes - plastic recycling classification number 2 (rigid plastics)
Packaging	Minimal - all packaging materials are recyclable
FDA Device Class	Class 1
FDA Regulatory Number	880.6785
European Device Class	Class 1
European Regulation	Medical Device Directive 93/42/EEC
GMDN Code	37163
Coefficient of Friction*	.21 static
Force Required **	37 lbs to move a 50th percentile male (178 lbs) using Pink Slip® (when using two care givers this would be 18.5 lbs each)
Force Required **	52 lbs to move a 90th percentile male (249 lbs) using Pink Slip® (when using two care givers this would be 26 lbs each)



*Coefficient of Friction (COF) was calculated from empirical data using a Hill-Rom P565ca3 Comfortline® Basic Mattress. Force measurements were recorded with a Chatillon DFE-200 Series Digital Dynamometer. The COF may vary depending upon the surface immersion rate. Softer or more compliant surfaces allow more immersion while firmer, less compliant surfaces allow less immersion.

**Movement Methodology: Caregiver(s) maintaining good ergonomic posture applied the effort necessary to pull the patient horizontally from a bed to a gurney. Force recorded was maximum force reading from Dynamometer.



1-633058-R05

800.255.3126 | wyeastmedical.com